



PRODUCT MANUAL

TRINITY SYSTEM

Thank you for choosing the K&K Trinity Pickup/Microphone Combination System!

In this installation packet, you will find:

- Trinity Microphone Installation (follows on p. 2)
- Pure Pickup installation (separate manual)
- Preamp installation and use (separate manual)

TRINITY MICROPHONE

1. Cut a 2 1/2" piece of the supplied dual-lock and locate the base of the gooseneck (gooseneck is thicker and stiffer than the mic cable). Loop the dual-lock piece around the base of the gooseneck. Pinch the sticky sides together to get a tab as shown in fig. 1.
2. Cut a second piece of dual-lock approx. 1" long (see fig. 2) and stick it to a suitable spot inside your guitar close to the edge of the sound hole (fig. 3).
3. Form the gooseneck to achieve a mic position as shown in fig. 3. This position is recommended to avoid picking directly over the mic. The mic should aim outwards, towards the strings, between the G and B string. The distance between strings and mic should be about 3/8 inch (ca 10 mm).
4. Press the dual-lock mic tab onto the second dual-lock piece inside your guitar and re-adjust the mic's gooseneck.(fig. 3) The dual-lock works like "super" velcro and can be re-opened.
5. You have the option to experiment with different mic angles and positions to obtain your personal best sound.
6. Secure all wiring inside guitar with tape.

