

## Specification

Nominal Basket Diameter	10", 254mm
Nominal Impedance*	8 ohms
Power Rating**	350W
Resonance	66Hz
Usable Frequency Range***	63Hz-3.7kHz
Sensitivity	98.8
Magnet Weight	56 oz.
Gap Height	0.375", 9.53mm
Voice Coil Diameter	2.5", 63.5mm

## Thiele & Small Parameters

Resonant Frequency (fs)	66Hz
DC Resistance (Re)	5.42
Coil Inductance (Le)	0.74mH
Mechanical Q (Qms)	6.53
Electromagnetic Q (Qes)	0.35
Total Q (Qts)	0.33
Compliance Equivalent Volume (Vas)	30.5 liters / 1.1 cu.ft.
Peak Diaphragm Displacement Volume (Vd)	121cc
Mechanical Compliance of Suspension (Cms)	0.18mm/N
BL Product (BL)	14.4 T-M
Diaphragm Mass inc. Airlod (Mms)	32 grams
Efficiency Bandwidth Product (EBP)	189
Maximum Linear Excursion (Xmax)	3.5mm
Surface Area of Cone (Sd)	344.9 cm <sup>2</sup>
Maximum Mechanical Limit (Xlim)	9.4mm

## Mounting Information

Recommended Enclosure Volume	
Sealed	
Vented	12.7-37.9 liters/0.45-1.34 cu.ft.
Overall Diameter	10.09", 256.2mm
Baffle Hole Diameter	9.15", 232.4mm
Front Sealing Gasket	fitted as standard
Rear Sealing Gasket	fitted as standard
Mounting Holes Diameter	0.25", 6.4mm
Mounting Holes B.C.D.	9.66", 245.4mm
Depth	4.25", 108mm
Net Weight	10.8 lbs., 4.9 kg
Shipping Weight	12 lbs., 5.4 kg


## Materials of Construction

Aluminum voice coil  
Polyimide former  
Ferrite magnet  
Vented core  
Pressed steel basket  
Paper Cone  
Cloth cone edge  
Solid composition paper dust cap



## DELTA-10A American Standard Series

Recommended for professional audio and bass guitar applications as a woofer/mid-bass or mid-range in vented monitors, satellites and multi-way enclosures.



\* Please inquire about alternative impedances.

\*\* Multiple units exceed published rating evaluated under EIA 426A noise source and test standard while in a free-air, non-temperature controlled environment.

\*\*\* The average output across the usable frequency range when applying 1W/1M into the nominal impedance. ie: 2.83V/8ohms, 4V/16ohms.

Eminence response curves are measured under the following conditions: All speakers are tested at 1w/1m using a variety of test set-ups for the appropriate impedance | LMS using 0.25" supplied microphone (software calibrated) mounted 1m from wall/baffle | 2ft. X 2ft. baffle is built into the wall with the speaker mounted flush against a steel ring for minimum diffraction | Hafler P1500 Trans-Nova amplifier | 2700 cu.ft. chamber with fiberglass on all six surfaces (three with custom-made wedges)