

AZ 8928 Digital Sound Level Meter

- **DIGITAL DISPLAY WITH ANALOG GRAPH !**
- **AUTO / MANUAL RANGING !**
- **MAX HOLD, F/ S RESPONSE, A/ C WEIGHTING !**
- **ANALOG OUTPUT !**

FEATURES

- Digital display of sound level.
- Measurement frequency ranging 300 Hz to 8000 Hz.
- A & C weighting selectable.
- Quasi-Analog bar indicator : 1 dB display steps, 50dB display range, updated every 40ms.
- Auto or Manual ranging selectable.
- Fast & Slow response selectable.
- Maximum hold.
- Record Max./ Min.
- Microphone : 6mm (Dia.) electric condenser type.
- Auto power off : 20 min after non-operation.
- Low battery indicator.
- Monitor the sound levels from traffic noise, alarm systems and workplace machinery.



SPECIFICATIONS

Function	Specification
Measuring Range	A Weighting : 40 dB ~ 130 dB C Weighting : 45 dB ~ 130 dB
Accuracy at 94dB, 1kHz	± 2dB
Analog output	AC 0.707 Vrms (F/S)
Quasi-Analog Bar Indicator	1 dB display step, 30 dB display range, Updated every 50 mS
Microphone	6mm Dia. Electric condenser microphone
Operating Temp./Humidity	Temperature : 0 ~ 50 °C , Humidity : 10 ~ 90 %RH
Storage Temperature	-20 ~ 60 °C
Special Function	Auto power off(approx. 20 min.), Record: Max. hold, Data hold: Max./Min.,
Battery Use / Life	9V x 1 / 30 Hrs typical
Dimension / Weight	72 x 182 x 30 mm / 150 g
Standard Accessories	Battery 9V x 1, Manual

Importer (Exclusive agent in Korea)

Dagatronics Corporation

263-1, Duckidong, Ilsan, Koyang, Kyungkido, Korea

TEL: (031) 916-8005 FAX: (031) 916-8080

E-mail: sale@buytnm.com Website: www.buytnm.com