



MD 46 Handheld Dynamic ENG/EFP Microphone

Designed for audio journalists and field reporters, the Sennheiser MD 46 offers a host of advantages. Its extended frequency response provides clarity that exceeds any comparable mic in its class, and its dimensions and weight ratio lend a completely comfortable feel. Add the fact that it's rugged enough to stand the strain of ENG/EFP, and you have a dynamic winner

Features—Benefits

- Rugged all metal body
- Extremely low sensitivity to handling noise
- Very insensitive to pop and wind noise
- Uniform frequency response
- Excellent sound quality
- Integral microphone clamp thread

Technical Data

Acoustic principle	pressure gradient transducer
Frequency response	40–18,000 Hz
Pick-up pattern	cardioid
Rejection at 1 kHz at 180 degrees	>20dB
Sensitivity at 1kHz	2.0mV/Pa+2.5dB (= - 54dB mit 0dB=1V/Pa) (= - 74dB mit 0dB=1V/ubar) (USA)
Nominal impedance at 1kHz	350 Ohm
Min. terminating impedance	1000 Ohm
Magnetic field at 50 Hz	<=1uV/uT
Dimensions in inches	1.92 x 9.84
Weight	12.7oz

Optional Accessories

Table stand	MZT 100
Foam windshield	MZW 416-1 MZW 421

Architect's Specifications

Omni-directional reporter's microphone, frequency response 40–18,000 Hz, sensitivity (free field, no load) 1.8 mV/Pa ± 2.5 dB at 1 kHz, nominal impedance 200 , min. terminating impedance 200 , dimensions 11.92 x 9.84 inches, weight approx. 12.7oz.

Sennheiser Electronic Corporation, 1 Enterprise Drive, Old Lyme, CT 06371
 Telephone: 860-434-9190 • Fax: 860-434-1759 • Web: <http://www.sennheiserusa.com>
Sennheiser Mexico: Av. Xola 613, PH6, Col. Del Valle 03100, Mexico, DF. Telephone: (525) 639-0956. Fax: (525) 639-9482
Sennheiser Canada: 221 Labrosse Ave, Pte-Claire, PQ H9R 1A3. Telephone: 514-426-3013. Fax: 514-426-3953
 Manufacturing Plant: Am Labor 1, 30900 Wedemark, Germany