



## DE250

### HF Drivers - 1 Inches

120 W continuous program power capacity  
 1' horn throat diameter  
 44 mm (1.7 in) aluminium voice coil  
 Polyimide diaphragm  
 1000 - 18000 Hz response  
 108.5 dB sensitivity

#### Specification

Throat Diameter	25 mm (1 in)
Nominal Impedance	8 ohm
Minimum Impedance	7.8 ohm
Continuous Power Handling	120 W
Nominal Power Handling (AES)	60 W
Sensitivity (1W/1m)	108.5 dB
Frequency Range	1 - 18 kHz
Recommended Crossover	1.6 kHz
Voice Coil Diameter	44 mm (1.7 in)
Winding Material	Aluminium
Inductance	0.11 mH
Diaphragm material	Polyimide
Flux Density	1.85 T
Magnet Material	Ceramic

#### Mounting & Shipping

Shipping Box (8 units)	260x260x190 mm (10.2x10.2x7.5 in)
Replacement Diaphragm	MMDDE2508

#### Mounting & Shipping

Overall Diameter	120 mm (4.7 in)
Depth	62 mm (2.4 in)
Net Weight	2.1 kg (4.6 lb)
Shipping Weight (8 units)	17.5 kg (38.5 lb)