


In-ceiling speaker DE200



- One-piece 2-way in-ceiling loudspeaker
- with Kevlar membrane and ball-proof decorative grille
- Ideal for use in department stores, restaurants and offices
- suitable for installation in ceilings of all kinds
- high sound quality and balanced frequency response
- well suited for background music









EN

Power handling	30 W	
Impedance	8 Ω	
Sound pressure level	110 dB max.	
Frequency response	60 – 22.000 Hz	
Dispersion angle	160°	
Dimensions	Ø 252 × 120 mm	
Ceiling cut-out	215 – 230 mm	
Weight	2.5 kg	
Colour	White RAL 9010	

This device is used to convert electrical low frequency signals into acoustic. Any other use or use under other operating conditions is considered to be improper and may result in personal injury or property damage. No liability will be assumed for damages resulting from improper use.

Ensure that plastic bags, packaging, etc. are properly disposed of and are not in the reach of babies and young children. Choking hazard! Ensure that children do not detach any small parts (e.g. knobs or the like) from the product. They could swallow the pieces and choke! Never let children use electrical devices unattended. For the transport and protective packaging, environmentally friendly materials have been chosen that can be supplied to normal recycling. Ensure that plastic bags, packaging, etc. are properly disposed of. Do not just dispose of these materials with your normal household waste, but make sure that they are collected for recycling. Please follow the notes and markings on the packaging.



country. If in doubt, consult your local waste disposal facility.

Thomann GmbH Hans-Thomann-Str. 1 • 96138 Burgebrach Germany • www.thomann.de

