

  
STAIRVILLE

Wild Wash  
9x3W LED UV BK DMX  
9x3W LED UV WH DMX  
LED floodlight

Musikhaus Thomann  
Thomann GmbH  
Hans-Thomann-Straße 1  
96138 Burgebrach  
Germany  
Telephone: +49 (0) 9546 9223-0  
E-mail: [info@thomann.de](mailto:info@thomann.de)  
Internet: [www.thomann.de](http://www.thomann.de)

17.04.2018, ID: 426835, 426836

# Table of contents

<b>1</b>	<b>General notes</b> .....	<b>5</b>
1.1	Further information.....	6
1.2	Notational conventions.....	7
1.3	Symbols and signal words.....	7
<b>2</b>	<b>Safety instructions</b> .....	<b>10</b>
<b>3</b>	<b>Features</b> .....	<b>15</b>
<b>4</b>	<b>Installation</b> .....	<b>16</b>
<b>5</b>	<b>Starting up</b> .....	<b>19</b>
<b>6</b>	<b>Connections and controls</b> .....	<b>21</b>
<b>7</b>	<b>Operating</b> .....	<b>23</b>
7.1	Starting the device.....	23
7.2	Main menu.....	23
7.3	Menu overview.....	25
7.4	Functions in DMX mode 2Ch-1.....	26
7.5	Functions in DMX mode 2Ch-2.....	26

7.6	Functions in DMX mode 11Ch.....	27
<b>8</b>	<b>Technical specifications.....</b>	<b>29</b>
<b>9</b>	<b>Plug and connection assignments.....</b>	<b>30</b>
<b>10</b>	<b>Troubleshooting.....</b>	<b>31</b>
<b>11</b>	<b>Cleaning.....</b>	<b>33</b>
<b>12</b>	<b>Protecting the environment.....</b>	<b>34</b>

# 1 General notes

This manual contains important instructions for the safe operation of the unit. Read and follow the safety instructions and all other instructions. Keep the manual for future reference. Make sure that it is available to all those using the device. If you sell the unit please make sure that the buyer also receives this manual.

Our products are subject to a process of continuous development. Thus, they are subject to change.

## 1.1 Further information

On our website ([www.thomann.de](http://www.thomann.de)) you will find lots of further information and details on the following points:

Download	This manual is also available as PDF file for you to download.
Keyword search	Use the search function in the electronic version to find the topics of interest for you quickly.
Online guides	Our online guides provide detailed information on technical basics and terms.
Personal consultation	For personal consultation please contact our technical hotline.
Service	If you have any problems with the device the customer service will gladly assist you.

## 1.2 Notational conventions

This manual uses the following notational conventions:

### Letterings

The letterings for connectors and controls are marked by square brackets and italics.

**Examples:** *[VOLUME]* control, *[Mono]* button.



### Displays

Texts and values displayed on the device are marked by quotation marks and italics.

**Examples:** *'24ch'*, *'OFF'*.


## 1.3 Symbols and signal words

In this section you will find an overview of the meaning of symbols and signal words that are used in this manual.

Signal word	Meaning
<b>DANGER!</b>	This combination of symbol and signal word indicates an immediate dangerous situation that will result in death or serious injury if it is not avoided.
<b>WARNING!</b>	This combination of symbol and signal word indicates a possible dangerous situation that can result in death or serious injury if it is not avoided.
<b>NOTICE!</b>	This combination of symbol and signal word indicates a possible dangerous situation that can result in material and environmental damage if it is not avoided.
Warning signs	Type of danger
	Warning – high-voltage.
	Warning – suspended load.



---

Warning signs	Type of danger
	Warning – danger zone.

Wild Wash 9x3W LED UV BK DMX 9x3W LED UV WH DMX

## 2 Safety instructions

### **Intended use**

This device is intended to be used as an electronic illumination effect using LED technics. The device is designed for professional use and is not suitable for use in households. Use the device only as described in this user manual. Any other use or use under other operating conditions is considered to be improper and may result in personal injury or property damage. No liability will be assumed for damages resulting from improper use.

This device may be used only by persons with sufficient physical, sensorial, and intellectual abilities and having corresponding knowledge and experience. Other persons may use this device only if they are supervised or instructed by a person who is responsible for their safety.

**Safety****DANGER!****Danger for children**

Ensure that plastic bags, packaging, etc. are disposed of properly and are not within reach of babies and young children. Choking hazard!

Ensure that children do not detach any small parts (e.g. knobs or the like) from the unit. They could swallow the pieces and choke!

Never let children unattended use electrical devices.

**DANGER!****Electric shock caused by high voltages inside**

Within the device there are areas where high voltages may be present. Never remove any covers.

There are no user-serviceable parts inside.

Do not use the device if covers, protectors or optical components are missing or damaged.



### **DANGER!**

#### **Electric shock caused by short-circuit**

Always use proper ready-made insulated mains cabling (power cord) with a protective contact plug. Do not modify the mains cable or the plug. Failure to do so could result in electric shock/death or fire. If in doubt, seek advice from a registered electrician.



### **WARNING!**

#### **Eye damage caused by high light intensity**

Never look directly into the light source.



### **WARNING!**

#### **Risk of epileptic shock**

Strobe lighting can trigger seizures in photosensitive epilepsy. Sensitive persons should avoid looking at strobe lights.



**NOTICE!**

**Risk of fire**

Do not block areas of ventilation. Do not install the device near any direct heat source. Keep the device away from naked flames.



**NOTICE!**

**Operating conditions**

This device has been designed for indoor use only. To prevent damage, never expose the device to any liquid or moisture. Avoid direct sunlight, heavy dirt, and strong vibrations.



### **NOTICE!**

#### **Power supply**

Before connecting the device, ensure that the input voltage (AC outlet) matches the voltage rating of the device and that the AC outlet is protected by a residual current circuit breaker. Failure to do so could result in damage to the device and possibly injure the user.

Unplug the device before electrical storms occur and when it is unused for long periods of time to reduce the risk of electric shock or fire.

### 3 Features

The LED floodlight is particularly suitable for lighting applications in clubs and discotheques, on rock stages, in theatres and musicals. It can also be used for effect lighting of stage backgrounds.

Special features of the device:

- Equipped with 9 × 3 watt UV LEDs
- Control via DMX (2 or 11 channels) as well as buttons and display on the unit
- Built-in automatic show programmes
- Sound control
- Robust metal housing with compact design
- Versatile installation and mounting options using the included mounting bracket
- Housing colour: black (item no. 426835) or white (item no. 426836)

## 4 Installation

Unpack and carefully check that there is no transportation damage before using the unit. Keep the equipment packaging. To fully protect the device against vibration, dust and moisture during transportation or storage use the original packaging or your own packaging material suitable for transport or storage, respectively.

You can install the device standing or hanging. When in use, the device must be mounted at a solid surface or clamped to an approved truss.

Work from a stable platform whenever you install or move the device or when you perform any kind of maintenance. Block access under the work area.



### **WARNING!**

#### **Risk of injury caused by falling objects**

Make sure that the installation complies with the standards and rules that apply in your country. Always secure the device with a secondary safety attachment, such as a safety cable or a safety chain.





**NOTICE!**

**Risk of overheating**

Always ensure sufficient ventilation.

The ambient temperature must always be below 40 °C (104 °F).



**NOTICE!**

**Possible data transmission errors**

For error-free operation make use of dedicated DMX cables and do not use ordinary microphone cables.

Never connect the DMX input or output to audio devices such as mixers or amplifiers.




*Please note that this device must not be connected to a dimmer.*

## 5 Starting up

Create all connections while the device is off. Use the shortest possible high-quality cables for all connections. Take care when running the cables to prevent tripping hazards.


### Connections in DMX mode

Connect the DMX input of the device to the DMX output of a DMX controller or another DMX device. Connect the output of the first DMX device to the input of the second one, and so on to form a daisy chain. Always ensure that the output of the last DMX device in the daisy chain is terminated with a resistor ( $110\ \Omega$ ,  $\frac{1}{4}\ \text{W}$ ).



## 6 Connections and controls

### Rear panel



Wild Wash 9x3W LED UV BK DMX 9x3W LED UV WH DMX

1	Safety eyelet for fastening the safety cable.
2	<i>[DMX IN]</i> : DMX input socket for connection to a DMX controller. <i>[DMX OUT]</i> : DMX output socket for connecting additional devices in the DMX chain.
3	Locking screws for locking the floodlight in the desired orientation.
4	Display and control buttons: <i>[MENU]</i> : Activates the main menu and toggles between menu items. <i>[UP]</i> : Increases the displayed value by one. <i>[DOWN]</i> : Decreases the displayed value by one. <i>[ENTER]</i> : Selects an option of the respective operating mode.
5	IEC chassis plug for the mains cable with fuse holder.
6	Bracket for floor placement or hanging.

## 7 Operating

### 7.1 Starting the device

Connect the device to the power supply to start operation. The display shows 'A001' for a few seconds, then the device is ready for operation.

### 7.2 Main menu

#### DMX address

This setting is only relevant if the device is controlled via a DMX controller.

Press *[MODE]* repeatedly until 'Addr' appears in the display. Press *[ENTER]*, then use *[UP]* and *[DOWN]* to select the desired DMX address between 1 ('A001') and 512 ('A512') and confirm with *[ENTER]*.

#### DMX mode

This setting is only relevant if the device is controlled via a DMX controller.

Press *[MODE]* repeatedly until 'Chnd' appears in the display. Press *[ENTER]*, then use *[UP]* and *[DOWN]* to select the desired DMX mode (2CH1, 2CH2 or 11CH) and confirm with *[ENTER]*.

### **Auto show**

Press *[MODE]* repeatedly until 'Show' appears in the display. Press *[ENTER]*, then use *[UP]* and *[DOWN]* to select the desired automatic light pattern between 0 ('Sh 0') and 15 ('Sh15') and confirm with *[ENTER]*.

### **Speed**

Press *[MODE]* repeatedly until 'SPEE' appears in the display. Press *[ENTER]*, then use *[UP]* and *[DOWN]* to select the desired running speed for the auto show between 0 ('SP 0') and 99 ('SP99') and confirm with *[ENTER]*.

### **Sound control**

Press *[MODE]* repeatedly until 'Soun' appears in the display. Press *[ENTER]*, then use *[UP]* and *[DOWN]* to select whether the device has to operate sound-controlled ('on') or not ('off'). Confirm with *[ENTER]*.

### **Sensitivity**

Press *[MODE]* repeatedly until 'SENS' appears in the display. Press *[ENTER]*, then use *[UP]* and *[DOWN]* to select the desired sensitivity of the built-in sound control microphone between 0 ('0') and 99 ('99') and confirm with *[ENTER]*.

### **Firmware version**


Press *[MODE]* repeatedly until 'vEr' appears in the display. Press *[ENTER]* to let the display show the currently used firmware version. Confirm with *[ENTER]*.



**Temperature**

Press [MODE] repeatedly until 'tEMP' appears in the display. Press [ENTER] to let the display show the current temperature inside the housing. Confirm with [ENTER].

**7.3 Menu overview**



## 7.4 Functions in DMX mode 2Ch-1

Channel	Value	Function
1	0 ... 255	Brightness of all LEDs (0 % to 100 %)
2	0 ... 9	No strobe effect
	10 ... 255	Strobe effect, increasing frequency

## 7.5 Functions in DMX mode 2Ch-2


Channel	Value	Function
1	0 ... 9	All LEDs off
	10 ... 255	Auto show selection
2	0 ... 249	Auto show speed, slow to fast
	250 ... 255	Sound-controlled auto show

## 7.6 Functions in DMX mode 11Ch

Channel	Value	Function
1	0 ... 255	Brightness of all LEDs (0 % to 100 %)
2	0 ... 9	No strobe effect
	10 ... 255	Strobe effect, slow to fast
3	0 ... 255	Brightness LED 1 (0 % to 100 %)
4	0 ... 255	Brightness LED 2 (0 % to 100 %)
5	0 ... 255	Brightness LED 3 (0 % to 100 %)
6	0 ... 255	Brightness LED 4 (0 % to 100 %)
7	0 ... 255	Brightness LED 5 (0 % to 100 %)
8	0 ... 255	Brightness LED 6 (0 % to 100 %)
9	0 ... 255	Brightness LED 7 (0 % to 100 %)

Channel	Value	Function
10	0 ... 255	Brightness LED 8 (0 % to 100 %)
11	0 ... 255	Brightness LED 9 (0 % to 100 %)

## 8 Technical specifications



Number of DMX channels	2 or 11 channels, depending on operating mode
Illuminant	9 × UV LEDs, 3 W each
Wave length	398 nm
Beam angle	approx. 110°
Operating supply voltage	100 - 240 V ~ 50/60 Hz
Power consumption	34 W
Housing colour	black (item no. 426835) white (item no. 426836)
Fuse	5 mm × 20 mm, 2 A, 250 V, fast-acting
Dimensions (W × H × D)	350 mm × 125 mm × 75 mm
Weight	1.3 kg

Wild Wash 9x3W LED UV BK DMX 9x3W LED UV WH DMX

## 9 Plug and connection assignments

### Introduction

This chapter will help you select the right cables and plugs to connect your valuable equipment so that a perfect light experience is guaranteed.

Please take our tips, because especially in 'Sound & Light' caution is indicated: Even if a plug fits into a socket, the result of an incorrect connection may be a destroyed DMX controller, a short circuit or 'just' a not working light show!

### DMX connections



The unit offers a 3-pin XLR socket for DMX output and a 3-pin XLR plug for DMX input. Please refer to the drawing and table below for the pin assignment of a suitable XLR plug.

Pin	Configuration
1	Ground, shielding
2	Signal inverted (DMX-, 'cold signal')
3	Signal (DMX+, 'hot signal')

## 10 Troubleshooting



### **NOTICE!**

#### **Possible data transmission errors**

For error-free operation make use of dedicated DMX cables and do not use ordinary microphone cables.

Never connect the DMX input or output to audio devices such as mixers or amplifiers.

In the following we list a few common problems that may occur during operation. We give you some suggestions for easy troubleshooting:

Symptom	Remedy
The unit does not work, no light, the display is dark	Check the mains connection and the main fuse.
No response to the DMX controller	1. Check whether the DMX controller is switched on. Check the DMX connectors and cables for proper connection.
	2. Check the address settings and the DMX polarity.
	3. Try using another DMX controller.
	4. Check whether the DMX cables run near or parallel to high-voltage cables that may cause damage or interference to a DMX interface circuit.

If the procedures recommended above do not succeed, please contact our Service Center. You can find the contact information at [www.thomann.de](http://www.thomann.de).



# 11 Cleaning

## Optical lenses

Clean the optical lenses, that are accessible from the outside, regularly in order to optimize the light output. The frequency of cleaning depends on the operating environment: wet, smoky or particularly dirty surroundings can cause more accumulation of dirt on the optics of the device.

- Clean with a soft cloth using our lamp and lens cleaner (item no. 280122).
- Always dry the parts carefully.

## Fan grids

The fan grids of the device must be cleaned on a regular basis to remove dust and dirt. Before cleaning, switch off the device and disconnect AC-powered devices from the mains. Use a lint-free damp cloth for cleaning. Never use solvents or alcohol for cleaning.

## 12 Protecting the environment

### Disposal of the packaging material



For the transport and protective packaging, environmentally friendly materials have been chosen that can be supplied to normal recycling.

Ensure that plastic bags, packaging, etc. are properly disposed of.

Do not just dispose of these materials with your normal household waste, but make sure that they are collected for recycling. Please follow the notes and markings on the packaging.

### Disposal of your old device



This product is subject to the European Waste Electrical and Electronic Equipment Directive (WEEE) in its currently valid version. Do not dispose with your normal household waste.

Dispose of this device through an approved waste disposal firm or through your local waste facility. When discarding the device, comply with the rules and regulations that apply in your country. If in doubt, consult your local waste disposal facility.



