

User Manual

*Harley Benton*

HB-40R

Guitar Combo

Thomann GmbH

Hans-Thomann-Straße 1

96138 Burgebrach

Germany

Telephone: +49 (0) 9546 9223-0

Internet: [www.thomann.de](http://www.thomann.de)

18.08.2022, ID: 147168 (V6)

---

## Table of contents

<b>1</b>	<b>General information.....</b>	<b>5</b>
	1.1 Further information.....	6
	1.2 Notational conventions.....	6
	1.3 Symbols and signal words.....	7
<b>2</b>	<b>Safety instructions.....</b>	<b>9</b>
<b>3</b>	<b>Features.....</b>	<b>12</b>
<b>4</b>	<b>Installation and starting up.....</b>	<b>13</b>
<b>5</b>	<b>Connections and controls.....</b>	<b>14</b>
<b>6</b>	<b>Technical specifications.....</b>	<b>17</b>
<b>7</b>	<b>Plug and connection assignment.....</b>	<b>19</b>
<b>8</b>	<b>Cleaning.....</b>	<b>21</b>
<b>9</b>	<b>Protecting the environment.....</b>	<b>22</b>



**4** HB-40R  
Guitar Combo

# 1 General information

This user manual contains important information on the safe operation of the device. Read and follow all safety notes and all instructions. Save this manual for future reference. Make sure that it is available to all persons using this device. If you sell the device to another user, be sure that they also receive this manual.

Our products and user manuals are subject to a process of continuous development. We therefore reserve the right to make changes without notice. Please refer to the latest version of the user manual which is ready for download under [www.thomann.de](http://www.thomann.de).

### 1.1 Further information

On our website ([www.thomann.de](http://www.thomann.de)) you will find lots of further information and details on the following points:

Download	This manual is also available as PDF file for you to download.
Keyword search	Use the search function in the electronic version to find the topics of interest for you quickly.
Online guides	Our online guides provide detailed information on technical basics and terms.
Personal consultation	For personal consultation please contact our technical hotline.
Service	If you have any problems with the device the customer service will gladly assist you.

### 1.2 Notational conventions

This manual uses the following notational conventions:

## Letterings



The letterings for connectors and controls are marked by square brackets and italics.

**Examples:** *[VOLUME]* control, *[Mono]* button.

## 1.3 Symbols and signal words

In this section you will find an overview of the meaning of symbols and signal words that are used in this manual.

Signal word	Meaning
<b>DANGER!</b>	This combination of symbol and signal word indicates an immediate dangerous situation that will result in death or serious injury if it is not avoided.
<b>CAUTION!</b>	This combination of symbol and signal word indicates a possible dangerous situation that can result in minor injury if it is not avoided.
<b>NOTICE!</b>	This combination of symbol and signal word indicates a possible dangerous situation that can result in material and environmental damage if it is not avoided.

Warning signs	Type of danger
 A yellow triangular warning sign with a black border and a black lightning bolt symbol in the center.	Warning – high-voltage.
 A yellow triangular warning sign with a black border and a black exclamation mark in the center.	Warning – danger zone.



## 2 Safety instructions

### Intended use

This device is intended to be used for amplification and playback of signals from musical instruments with electromagnetic pickups. Any other use or use under other operating conditions is considered to be improper and may result in personal injury or property damage. No liability will be assumed for damages resulting from improper use.

This device may be used only by persons with sufficient physical, sensorial, and intellectual abilities and having corresponding knowledge and experience. Other persons may use this device only if they are supervised or instructed by a person who is responsible for their safety.

### Safety



#### **DANGER!**

#### **Danger for children**

Ensure that plastic bags, packaging, etc. are disposed of properly and are not within reach of babies and young children. Choking hazard! Ensure that children do not detach any small parts (e.g. knobs or the like) from the unit. They could swallow the pieces and choke! Never let children unattended use electrical devices.



#### **DANGER!**

#### **Electric shock caused by high voltages inside**

Within the device there are areas where high voltages may be present. Never remove any covers. There are no user-serviceable parts inside. Do not use the device if covers, protectors or optical components are missing or damaged.

**DANGER!****Electric shock caused by short-circuit**

Do not modify the mains cable or the plug. Failure to do so could result in electric shock/death or fire. If in doubt, seek advice from a registered electrician.

**CAUTION!****Possible hearing damage**

The device can produce volume levels that may cause temporary or permanent hearing impairment. Over an extended period of time, even levels that seem to be uncritical can cause hearing damage. Decrease the volume level immediately if you experience ringing in your ears or hearing impairment. If this is not possible, keep a greater distance or use sufficient ear protectors.

**CAUTION!****Possible hearing damage**

Using headphones for a prolonged period and at high volume can cause hearing damage. Avoid using the device at high volume, especially when using headphones.

**NOTICE!****Risk of fire**

Do not block areas of ventilation. Do not install the device near any direct heat source. Keep the device away from naked flames.

**NOTICE!****Operating conditions**

This device has been designed for indoor use only. To prevent damage, never expose the device to any liquid or moisture. Avoid direct sunlight, heavy dirt, and strong vibrations. Only operate the device within the ambient conditions specified in the chapter 'Technical specifications' of this user manual. Avoid heavy temperature fluctuations and do not switch the device on immediately after it was exposed to temperature fluctuations (for example after transport at low outside temperatures). Dust and dirt inside can damage the unit. When operated in harmful ambient conditions (dust, smoke, nicotine, fog, etc.), the unit should be maintained by qualified service personnel at regular intervals to prevent overheating and other malfunction.



**NOTICE!**

**Power supply**

Before connecting the device, ensure that the input voltage (AC outlet) matches the voltage rating of the device and that the AC outlet is protected by a residual current circuit breaker. Failure to do so could result in damage to the device and possibly injure the user. Unplug the device before electrical storms occur and when it is unused for long periods of time to reduce the risk of electric shock or fire.



**NOTICE!**

**Possible staining**

The plasticiser contained in the rubber feet of this product may possibly react with the coating of your surface and after some time cause permanent dark stains. In case of doubt, do not put the rubber feet directly on the surface and use a suitable underlay if necessary, i.e. felt pads or similar.

## 3 Features

### Special features of the device

- Output power 40 watt
- 10" speaker
- Overdrive switch
- 3-band equalizer
- Built-in reverb effect
- Inputs
  - Input
  - Aux
  - Footswitch
- Outputs
  - Headphones
  - Line
  - Ext. Speaker
- Standby function

## 4 Installation and starting up

Unpack and check carefully there is no transportation damage before using the unit. Keep the equipment packaging. To fully protect the product against vibration, dust and moisture during transportation or storage use the original packaging or your own packaging material suitable for transport or storage, respectively.

Create all connections while the device is off. Use the shortest possible high-quality cables for all connections. Take care when running the cables to prevent tripping hazards.





### **NOTICE!**

#### **Possible property damage by magnetic fields**

Loudspeakers produce a static magnetic field. Therefore, maintain an appropriate distance to devices that can be adversely affected or damaged by an external magnetic field.

## 5 Connections and controls



1	<i>[INPUT]</i>   1/4" jack socket to connect your instrument
2	<i>[CHANNEL SELECT]</i>   switch to toggle between clean and overdrive channel
3	Channel indicator. Lights up green when the overdrive channel is active.
4	<i>[GAIN]</i>   control to adjust the signals preamp gain
5	<i>[VOLUME]</i>   control to adjust the volume of the overdrive channel
6	<i>[VOLUME]</i>   control to adjust the volume of the clean channel
7	<i>[TREBLE]</i>   control to adjust the treble
8	<i>[MIDDLE]</i>   control to adjust the mids
9	<i>[BASS]</i>   control to adjust the bass
10	<i>[REVERB]</i>   control to adjust the intensity of the reverb effect
11	Aux input for connecting an MP3 or CD player (3.5 mm mini phone socket).
12	Headphones output (3.5 mm mini phone socket). When you connect headphones, the internal speaker is automatically muted.
13	<i>[LINE OUT]</i>   output to connect an additional amplifier or recording device (3.5 mm mini phone socket)
14	<i>[FOOT SWITCH]</i>   input for an optional foot switch (1/4" phone socket). Use a foot switch to toggle between the channels of the amplifier.

- |    |   |
|----|---|
| 15 | Standby indicator   If there is no signal at the instruments input [ <i>INPUT</i> ] for 30 minutes, the device will automatically enter standby mode (LED green). As soon as the device receives a signal again at the instruments input [ <i>INPUT</i> ], the device automatically switches back to normal mode (LED red). |
| 16 | [ <i>POWER</i> ]   main switch. Turns the device on and off.  |
| 17 | Power cord  |
| 18 | [ <i>EXTERNAL SPEAKER</i> ]   output to connect an external speaker box (1/4" jack socket). The impedance of the external speaker must be at least 4 $\Omega$ . When you connect an external speaker box, the internal speaker is automatically muted.  |



## 6 Technical specifications

Speaker	1 × 10" speaker	
Input connections	Instruments	1/4" jack socket
	AUX	3.5 mm phone socket
	Optional foot switch	1/4" jack socket
Output connections	Headphones	3.5 mm phone socket
	Amplifier or recording device	3.5 mm phone socket
	External speakers (impedance min. 4 Ω)	1/4" jack socket
Input impedance	220 kΩ	
Output power	40 W (RMS) @ 4 Ω	
Frequency range	60 Hz to 12 kHz	
Signal-to-noise ratio	75 dB	
Total harmonic distortion (THD)	0.5% (Clean-Sound)	
Power consumption	max. 80 W	
Supply voltage	230 V ~ 50 Hz	
Dimensions (W × H × D)	425 mm × 420 mm × 220 mm	

## Technical specifications

---

Weight	10 kg	
Ambient conditions	Temperature range	0 °C...40 °C
	Relative humidity	20 %...80 % (non-condensing)

### Further information

Channels	2
Reverb	yes
Effects processor	no
External effects loop	no
Line input	no
Recording output	yes
MIDI port	no
External speaker connector	yes
Headphone connection	yes
Foot switch connector	yes
Incl. foot switch	no

## 7 Plug and connection assignment

### Introduction

This chapter will help you select the right cables and plugs to connect your valuable equipment in such a way that a perfect sound experience is ensured.

Please note these advices, because especially in 'Sound & Light' caution is indicated: Even if a plug fits into the socket, an incorrect connection may result in a destroyed power amp, a short circuit or 'just' in poor transmission quality!

### Balanced and unbalanced transmission

Unbalanced transmission is mainly used in semi-professional environment and in hifi use. Instrument cables with two conductors (one core plus shielding) are typical representatives of the unbalanced transmission. One conductor is ground and shielding while the signal is transmitted through the core.

Unbalanced transmission is susceptible to electromagnetic interference, especially at low levels, such as microphone signals and when using long cables.

In a professional environment, therefore, the balanced transmission is preferred, because this enables an undisturbed transmission of signals over long distances. In addition to the conductors 'Ground' and 'Signal', in a balanced transmission a second core is added. This also transfers the signal, but phase-shifted by 180°.

Since the interference affects both cores equally, by subtracting the phase-shifted signals, the interfering signal is completely neutralized. The result is a pure signal without any noise interference.

## 1/4" TS phone plug (mono, unbalanced)



1	Signal
2	Ground, shielding

## Three-pole 1/8" mini phone jack (stereo, unbalanced)



1	Signal (left)
2	Signal (right)
3	Ground, shielding

## 8 Cleaning

### Device components

Clean the device components that are accessible from the outside regularly. The cleaning frequency depends on the operating environment: damp, smoky or particularly dirty environments can cause greater accumulation of dirt on the device components.

- Clean with a dry soft cloth.
- Stubborn dirt can be removed with a slightly dampened cloth.
- Never use solvents or alcohol for cleaning.

## 9 Protecting the environment

### Disposal of the packaging material



For the transport and protective packaging, environmentally friendly materials have been chosen that can be supplied to normal recycling.

Ensure that plastic bags, packaging, etc. are properly disposed of.

Do not just dispose of these materials with your normal household waste, but make sure that they are collected for recycling. Please follow the notes and markings on the packaging.

### Disposal of your old device



This product is subject to the European Waste Electrical and Electronic Equipment Directive (WEEE) in its currently valid version. Do not dispose with your normal household waste.

Dispose of this device through an approved waste disposal firm or through your local waste facility. When discarding the device, comply with the rules and regulations that apply in your country. If in doubt, consult your local waste disposal facility.



