

TUBE ULTRAGAIN MIC100

Technical Specifications

Version 1.0 February 2003

ENGLISH



www.behringer.com



TUBE ULTRAGAIN

Vacuum Tube Preamplifier with Limiter

- ▲ High-end tube mic/line preamplifier for studio, live and hard disk recording applications
- ▲ Hand-selected 12AX7 vacuum tube with UTC technology for exceptional warmth and lowest noise
- ▲ The ultimate sound-enhancing tool for virtually any sound source
- ▲ Perfectly complements studio-grade condenser mics
- ▲ Usage as a high-end DI-box ensures outstanding signal integrity
- ▲ Eliminates the “dull” sound of standard digital recorders and sound cards
- ▲ Dynamic limiter effectively protects your equipment from overload
- ▲ Phase reverse switch, +48 V phantom power and 20 dB pad for utmost flexibility
- ▲ Balanced inputs and outputs on 1/4" TRS and gold-plated XLR connectors
- ▲ Highly accurate 8-segment LED level meter
- ▲ Extremely wide-range input gain and output level adjustment

W
M
I
G
I
O
O

SPECIFICATIONS

XLR INPUT

Connector	Balanced/unbalanced
Type	Transformerless, DC-decoupled input
Impedance	approx. 2 k Ω
Max. input level	+7 dBu / 20 dB with pad

1/4" TRS INPUT

Connector	Balanced/unbalanced
Type	Transformerless, DC-decoupled input
Impedance	approx. 1 M Ω
Max. input level	+16 dBu / 20 dB with pad

AUDIO OUTPUTS

Connectors	XLR and 1/4" TRS connector
Type	balanced/unbalanced Transformerless, DC-decoupled output
Impedance	approx. 700 Ω balanced / approx. 350 Ω unbalanced
Max. output level	approx. +26 dBu @ 100 k Ω

SYSTEM SPECIFICATIONS

Frequency response	Mic input <10 Hz - 43 kHz (+/-3 dB) Line input <10 Hz - 40 kHz (+/-3 dB)
--------------------	---

FUNCTION CONTROLS

Gain	variable (+26 to +60 dB)
Output	variable (- ∞ to +10 dB)

FUNCTION SWITCHES

20 dB pad	Level attenuation (20 dB)
+48 V	Activates the phantom power
Phase reverse	Phase reverse (180°)
Limiter	Limits the output signal

INDICATORS

Input level	8-segment LED meter: -24, -18, -12, -6, 0, +6, +12, clip
Power-LED	Indicates operation

POWER SUPPLY

Mains voltages	
USA/Canada	120 V~, 60 Hz, PSU
U.K./Australia	240 V~, 50 Hz, PSU
Europe	230 V~, 50 Hz, PSU
Japan	100 V~, 50 - 60 Hz, PSU

PHYSICAL

Dimensions (H x W x D)	approx. 2 1/2" (64 mm) x 5 1/4" (135 mm) x 5 1/4" (135 mm)
Weight	approx. 0.5 kg (1.1 lbs), without power supply

BEHRINGER continuously strives to assure the highest quality standards possible. Required modifications may be implemented without prior notice. Technical data and the appearance of the unit may deviate from the above values and/or illustrations.

The information contained in this publication is subject to change without notice. No part of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording of any kind, for any purpose, without the express written permission of BEHRINGER Spezielle Studiotechnik GmbH.

BEHRINGER and ULTRAGAIN are registered trademarks. ALL RIGHTS RESERVED.

© 2003 BEHRINGER Spezielle Studiotechnik GmbH.

BEHRINGER Spezielle Studiotechnik GmbH, Hanns-Martin-Schleyer-Str. 36-38, 47877 Willich-Münchheide II, Germany
Tel. +49 (0) 21 54 / 92 06-0, Fax +49 (0) 21 54 / 92 06-30
