

HS 2

Microphones | Headset Microphones

Cat. No. 005336

General Description

The HS 2 is an omni-directional headset microphone using an MKE 2 Gold capsule and fitted with a steel wire cable and a special 3-pin connector for Sennheiser 3000 and 5000 Series bodypack transmitters. The small capsule and gooseneck assembly can be optimally positioned for both vocal and speech applications. Also available as HS 2-1 in beige.



Technical Data

Pick-up pattern	omni-directional
Frequency response	20 – 20,000 Hz ± 3 dB
Sensitivity (free field, no load) (1 kHz)	5 mV/Pa ± 3 dB
Nominal impedance	1 kΩ
Min. terminating impedance	4.7 kΩ
Equivalent noise level	
A-weighted (DIN IEC 651)	26 dB
CCIR-weighted (CCIR 468-3)	39 dB
Max. SPL (1 kHz)	142 dB (THD = 1 %)
Power supply	18 kΩ/7.5 V
Connector	3-pin audio connector for SK 50/SK 250/SK 5012
Cable length	1.6 m (5.25 ft)
Capsule diameter	Ø 4.8 mm (0.19")
Weight	appx. 34 g (1.20 oz)

Features

- Frequency response optimised for close talking applications
- Lightweight design
- Flexible gooseneck for optimally positioning the microphone capsule
- Umbrella Diaphragm™ protects the mic against sweat

Product Variants

- HS 2-1: as HS 2, but beige
- HS 2-5: as HS 2, but with open-ended cable