

Gitarrenkabel Top Performance
Guitar Cable Top Performance

Stage
 Studio
 robust jacket
 low resistance
 low noise / lowest capacity



Bestellnummer	Part No.	CGK 175
Mechanische Daten	Mechanical data	
Leiterquerschnitt	Conductor area	0,75 m ²
Leiteraufbau	Composition of conductor	42 x 0,15 mm CU blank / bare copper
Leiterisolation	Conductor isolation	TPE
Adernanordnung	Composition of cores	-
Paarschirm / Schirm	Pair screen / screen	Geflecht aus bl. CU-Drähten + 1x Schirm aus leitendem Kunststoff / copper braid shield + 1x conductive plastic
Gesamtmantel	Overall jacket	PVC, black
Gesamtdurchmesser	Overall diameter	7,20 +/- 0,20 mm
Gewicht	Weight	ca. 60 g/m
Betriebstemperatur bewegt	Working temperature mobile	(-5°C) - (+70°C)
unbewegt	fixed	(-20°C) - (+70°C)
Elektrische Daten	Electrical data	
Leiterwiderstand	Conductor resistance	24,4 Ohm/km
Kapazität (Leiter / Leiter)	Capacity (cond./cond.)	76 pF/m
Kapazität (Leiter / Schirm)	Capacity (cond./screen)	-
Prüfspannung	Test voltage	500 V