

4088-B, 4088 Cardioid Headband

The best sounding directional headworn microphone on the market, the smooth and elegant 4088 is also the most invisible headworn cardioid microphone.

The mechanical design is based on the proven build quality of the 4066 headband microphone. The headband mount is exactly the same; the boom however is 3 centimeters longer, to be able to match the need for placement at the corner of the mouth. The flexibility and stability of this construction is unique and has no equal.

Available in three colors: black, beige and brown, and also available with connector.

Video: DPA 4088 cardioid headband on singer

Pop screens included
Five pop screens in the same color as the 4088 are enclosed. Additional pop screens are available:

- open and natural sound
- unequalled flexibility and stability
- available in three colors and three sizes

DUA0574	Pop	Screens	for	4088,	black,	5	pcs.
DUA0575	Pop	Screens	for	4088,	beige,	5	pcs.
DUA0576 Pop Screens for 4088, brown, 5 pcs.							

DPA 4088 is a miniature cardioid headband built on the finest DPA experiences in microphone design and manufacturing, providing the best sounding directional headworn microphone available today for performing talent of various sorts.

For more information please visit:
www.dpamicrophones.com

Open, natural and reliable are the most describing words for this microphone. The high quality of the microphone itself means, that you will hear the sound of the voice right away - not the microphone. In acoustically demanding live performance environments, where background noise and feedback is a concern, the 4088 will tackle these challenges with ease.

The smooth and elegant design of the 4088 makes it the most invisible headworn cardioid microphone today. Sound quality, visual elegance and versatility go hand in hand to transform every show into the performance of a lifetime. The capsule is a pre-polarized first order pressure gradient transducer, hidden in a small and lightweight housing with dimensions just slightly larger than our omni capsules.

4088-B, 4088 Cardioid Headband

Directional characteristics:

Cardioid

Principle of operation:

Pressure gradient

Cartridge type:

Pre-polarized condenser element with vertical diaphragm

Frequency range, ± 2 dB:

100 Hz – 20 kHz (4 – 6 dB soft boost at 15 kHz)

Sensitivity, nominal, ± 3 dB at 1 kHz:

6 mV/Pa; 44 dB re. 1 V/Pa

Equivalent noise level, A-weighted:

Typ. 26 dB(A) re. 20 μ Pa (max. 28 dB(A))

Equivalent noise level ITU-R BS.468-4:

Typ. 38 dB (max. 40 dB)

S/N ratio, re. 1 kHz at 1 Pa (94 dB SPL):

68 dB (A)

Total harmonic distortion (THD):

< 1 % up to 123 dB SPL peak; < 1 % up to 120 dB SPL RMS sine

Dynamic range:

Typ. 97 dB

Max. SPL, peak before clipping:

144 dB

Output impedance:

30 – 40 ohm

Cable drive capability:

Up to 300 m (984 ft)

Power supply:

For wireless systems: Min. 5 V – max. 50 V through DPA adapter. With DAD6001-BC/DAD6024/DAD4099: 48 V phantom power ± 4 V for full performance.

Connector:

MicroDot

Color:

Black, brown or beige

Microphone weight:

14 g (0.5 oz) incl. cable and MicroDot connector

Microphone diameter:

5.5 mm (0.25 in)

Microphone length:

11 mm (0.5 in)

Cable length:

1.2 m (3.9 ft)

Cable diameter:

1.6 mm (0.06 in)

Polarity:

Positively increasing sound pressure produces positive going voltage on MicroDot pin


Operating temperature range:

-10 to 45 °C (14 to 113 °F)

Diagrams


4088-B, 4088 Cardioid Headband

Frequency response of the DPA 4088



Frequency response of the DPA 4088

Directional Characteristics of DPA 4088



Directional Characteristics of DPA 4088



Headquarters:
DPA Microphones A/S
Gydevang 42-44
DK-3450 Allerød, Denmark
Tel: +45 4814 2828
Fax: +45 4814 2700
info@dpamicrophones.com
www.dpamicrophones.com

United States:
DPA Microphones, Inc.
2432 N. Main St., Suite 200
Longmont, CO 80501, USA
Tel: +1 303-485-1025
Fax: +1 303-485-6470
info-usa@dpamicrophones.com
www.dpamicrophones.com