

# NT1-A

The World's Quietest Studio Condenser Microphone

**RØDE**<sup>®</sup>  
MICROPHONES




## Features

- Large 1" (25mm) capsule with gold plated diaphragm
- Cardioid polar pattern
- Self noise of only 5dB (A)
- Ultra low noise, transformerless surface mount circuitry
- Wide dynamic range
- Gold plated output contacts
- True condenser (externally biased)
- Internal capsule shock mounting
- Designed and manufactured in Australia
- Full 10 year warranty\*


## Specifications

Acoustic Principle	Pressure gradient	Directional Pattern	Cardioid
Frequency Range	20 Hz-20 kHz	Sensitivity	-32 dB re 1 Volt/Pascal (25 mV @ 94 dB SPL) +/- 2 dB @ 1kHz
Output Impedence	100Ω	Dimensions	Length - 190mm (7.480") Diameter - 50mm (1.968")
Output Connection	3 pin XLR, balanced output between Pin 2 (+), Pin 3 (-) and Pin 1 (ground)	Shipping Weight	780gm
Net Weight	326g		

## Polar Pattern



## Frequency Response



## Included Accessories

- Single - SM1 shock mount and ZP1 zip pouch
- Matched Pair - 2 x SM1 shock mount, RC6 case



[www.rodemic.com](http://www.rodemic.com)

\*After online registration

Australia  
107 Carnarvon st, Silverwater NSW 2128 Australia  
Ph: +61 2 9648 5855 Fx: +61 2 9648 2455

USA  
PO Box 4189 Santa Barbara CA 93140 USA  
Ph: +1 805 566 7777 Fx: +1 805 566 0071