

Studio Monitors

BEHRITONE C50A/C5A

C50A — Active 30-Watt Full-Range Reference Studio Monitor

- High-resolution, 30-Watt active nearfield monitor
- Frequency response from 90 Hz to 17 kHz with zero crossover phase distortion
- 6 ½" cube cabinet with multiple coats of high-gloss piano lacquer finish

C5A — Vintage-Style 30-Watt Active Full-Range Reference Studio Monitor

- Vintage-style studio monitor modeled after a famous model from the 70's
- 6 ½" cube cabinet with detachable acoustic foam and attractive wood laminate

Common features:

- High-end 30-Watt Class-D amplifier built-in to perfectly match the speaker's performance
- Full-range 5 ¼" speaker with special diaphragm and deformation-resistant chassis
- Homogeneous dispersion pattern due to singular small-diaphragm full-range driver configuration
- Magnetic shielding allows placement near computer monitors
- Precision-milled, high-rigidity MDF cabinet and baffle for minimal resonance



BEHRITONE C5A and C50A full-range reference studio monitors let you hear what your mixes will sound like on real-world systems such as car stereos, computers, televisions, iPod stations and other bass-challenged systems. Each 6.5" cube contains its own dedicated 30-Watt Class-D power amp and a specially designed 5-¼" full-range speaker for crystal-clear audio reproduction. Both models accept balanced XLR and ¼" TRS, as well as unbalanced RCA connections, and are magnetically shielded so they won't disrupt your computer video monitors.

Beauty is More Than Just Skin-Deep

BEHRITONE loudspeakers are our homage to a now-defunct company and their legendary 5C loudspeakers, which literally shook up the recording industry in the 1970s and '80s. The original versions were passive little


vinyl-clad, particle-board cubes that recording engineers soon came to love. The C50A features a high-gloss piano lacquer finish, while the C5A sports a classic wood-grain laminate, allowing either model to fit into virtually any studio décor. Both are constructed of precision-milled, high-rigidity MDF for extremely low-resonance performance. A neoprene pad is included for superior acoustic isolation when the speakers are placed on a desktop, or the enclosures can be mounted on mic stands via the built-in ⅝" adapters.

Discover what world-class studio and mastering engineers have known for decades—the only way to get the TRUTH about your mix is to hear it through these pint-sized beauties. BEHRITONE C5A or C50A active studio monitors are the perfect complement to your current monitoring system.




BEHRITONE C50A/C5A

C50A Recording Setup



Computer Setup



BEHRITONE C50A/C5A

C50A/C5A

AUDIO INPUTS

XLR connector	Balanced input
¼" TRS	Balanced input
RCA	Unbalanced input
Input impedance	10 kΩ
Input trim	-6 dB to +6 dB
Max. input level	+20 dBu

TRANSDUCER

Full-range driver	5 ¼" speaker
-------------------	--------------

AMPLIFIER OUTPUT POWER

RMS @ 0.1 % THD (sine wave)	30 W @ 8 Ω
Peak power	36 W @ 8 Ω

SYSTEM SPECIFICATION

C50A

Frequency range	90 Hz to 17 kHz
-----------------	-----------------

C5A

Frequency range	150 Hz to 15 kHz
-----------------	------------------

POWER SUPPLY

C50A/C5A

Fuse

100 - 240 V~, 50/60 Hz	T 1.25 A H 250 V
Power consumption	56 W
Mains connection	Standard IEC connector

DIMENSIONS/WEIGHT

Dimensions (H x W x D)	6.5 x 6.5 x 7.8" 165 x 165 x 198 mm
------------------------	--

C50A

Weight	7.3 lbs / 3.3 kg
--------	------------------

C5A

Weight	7.1 lbs / 3.2 kg
--------	------------------

Please note these specifications are preliminary and conceptual in nature, and as such are subject to change as product development progresses. This information is supplied for market research purposes only and is not to be made public in any manner. This document is solely the property of The MUSIC Group, or one of its subsidiaries, and must be surrendered upon request of the owner.

For service, support or more information contact the BEHRINGER location nearest you:

Europe Tel.: +49 2154 9206 4149
Fax: +49 2154 9206 4199

USA/Canada Tel.: +1 425 672 0816
Fax: +1 425 673 7647

Singapore Tel.: +65 6845 1800
Fax: +65 6214 0275

Australia Tel.: +61 03 9877 7170
Fax: +61 03 9877 7870

Japan Tel.: +81 3 5281 1180
Fax: +81 3 5281 1181

©2011 Red Chip Company Ltd. Technical specifications and appearance subject to change without notice. The information contained herein is correct at the time of printing. All trademarks are the property of their respective owners. BEHRINGER accepts no liability for any loss which may be suffered by any person who relies either wholly or in part upon any description, photograph or statement contained herein. 985-10000-00492

behringer.com

