



STINGER15G²

15"/1" PASSIVE / POWERED MULTI-FUNCTIONAL SPEAKER

SPECIFICATIONS

| Model name: | LDEB152G2 | LDEB152AG2 |
|----------------------------------|---|---|
| Type: | Passive multi-functional speaker | Powered multi-functional speaker |
| Woofers size: | 15" | 15" |
| Woofers magnet: | Ferrit | Ferrit |
| Woofers brand: | Custom made | Custom made |
| Woofers voice coil: | 3" | 3" |
| Horn: | CD horn | CD horn |
| HF driver size: | 1" | 1" |
| HF driver magnet: | Ferrit | Ferrit |
| HF driver brand: | BMS | BMS |
| HF driver voice coil: | 1" | 1" |
| Amplification: | - | Class D, Hypex Ucd400 |
| Dispersion: | 100° x 55° | 100° x 55° |
| Rated system power (RMS / peak): | 500 W / 1000 W | 400 W / 800 W |
| Frequency range: | 50 Hz - 19 kHz | 50 Hz - 19 kHz |
| Max. SPL (continuous): | 127 dB | 120 dB |
| Impedance: | 8 Ohms | - |
| Protection: | HF driver | HF driver, short circuit, over-current |
| Input sensitivity: | - | -5 dBu |
| Controls: | - | Mic gain, line gain, volume, treble, bass, power |
| Indicators: | - | Protect, limit, signal, power |
| Line / mic inputs: | - | XLR/jack (combo) |
| Line Outputs: | - | XLR |
| Speaker connectors: | SPKn | SPKn / 8 Ohm |
| Power supply: | - | Switch-mode power supply |
| Operating power: | - | 230 V AC |
| Cabinet material: | 15 mm plywood | 15 mm plywood |
| Cabinet Surface: | Textured paint | Textured paint |
| Dimensions (W x H x D): | 480 x 650 x 460 mm | 480 x 650 x 460 mm |
| Weight: | 25,5 kg | 28,5 kg |
| Features: | LD Systems evolutive handles, vertically adjustable stand support (SM707), 6 x M8 | LD Systems evolutive handles, vertically adjustable stand support (SM707), 6 x M8 |