



- ✓ C-clamp for stage lighting
- ✓ 50 kg max. working load
- ✓ 175 mm × 90 mm × 25 mm
- ✓ also available in black



Construction and mounting:

The C-clamp is made of 25 mm × 6 mm cold-rolled steel.

The truss protection spring is attached by two iron rivets at the C-clamp. A wing nut M10 x 25 is used to secure the C-clamp to the truss.

For fastening of the lighting fixture, a screw M10 × 35 is used with appropriate nut M10, a 10 mm flat washer and a 10 mm spring washer.

The C-clamp is intended for use on trusses with a tube diameter of 30 mm to a maximum of 52 mm. Use the device only as described. Any other use or use under other operating conditions is considered to be improper and may result in personal injury or property damage. No liability will be assumed for damages resulting from improper use.

 Ensure that plastic bags, packaging, etc. are not within reach of babies and young children. Choking hazard! Ensure that children do not detach any small parts (e.g. knobs or the like) from the unit. They could swallow the pieces and choke! Never let children unattended use electrical devices.

 Die tightening power of the C-clamp-bolt on the truss should be about 20 N. Do not keep using the C-clamp if it shows damages.

 Check every 30 days, whether the C-clamp is still sitting firmly on the truss. Tighten the screws again firmly if necessary. Make sure that the C-clamp is not exposed to moisture for a longer period of time.

 For the transport and protective packaging, environmentally friendly materials have been chosen that can be supplied to normal recycling. Ensure that plastic bags, packaging, etc. are properly disposed of. Do not just dispose of these materials with your normal household waste, but make sure that they are collected for recycling. Please follow the notes and markings on the packaging.