Altea 400



ALTEA-415



DESCRIPTION

The ALTEA-415 and ALTEA-412 are passive systems designed for use with external amplification and an outboard DSP. They allow users to choose the powering option they prefer and benefit from the same enclosure features and top-of-the-line components as the ALTEA-400 powered versions.

The ALTEA-400 models use the renowned Mi Series loudspeakers. These professional-grade loudspeakers provide precise low frequency reproduction with excellent musicality. The high frequencies are handled by the M-32 compression driver with 1" exit to provide exceptional overall performance. A winning combination of matched components that offer ideal characteristics for music reproduction.

KEY FEATURES

- \cdot 2-way, full range system
- •15" bass loudspeaker
- \cdot 1" compression driver
- \cdot Angled enclosure design for stage monitor use
- Built-in rigging points
- \cdot Stand mountable

APPLICATIONS

 \cdot Concerts and corporate A/V

- Portable and live clubs
- \cdot Concert halls, theaters and auditoriums
- $\boldsymbol{\cdot}$ Houses of worship

SPECIFICATIONS

Performance

| Ferrormance | |
|-----------------------------|---|
| Frequency Range (-10 dB) | 63 Hz – 20 kHz |
| Horizontal Coverage (-6 dB) | 90° |
| Vertical Coverage | 60° |
| Nominal Impedance | 8 ohms |
| RMS Power Handling | 350 W |
| Peak Power Handling | 1400 W |
| On-axis Sensitivity 1W/I m | 96 dB SPL |
| Maximum Peak SPL at 1 m | 128 dB |
| Recommended Amplifier | PA-900 |
| Recommended Processor | DSP-226 |
| Connectors | |
| Audio Input Connector | 1 x speakON NL4 |
| Audio Output Connector | 1 x speakON NL4 |
| Enclosure | |
| Enclosure Construction | Polypropylene |
| Enclosure Geometry | Trapezoidal |
| Rigging | M8 Rigging Points |
| Color | Black |
| Depth | 380 mm (15,0 in) |
| Dimensions (H x W x D) | 710 x 440 x 380 mm 28,0 x 17,3 x 15,0 in |
| Net Weight | 16,5 kg (36,4 lb) |



ALTEA-415

Components

| LF Driver | 15MI |
|--|---|
| HF Driver | M-32 |
| Shipping Carton Dimensions (H x W x D) | 805 x 530 x 445 mm 31,7 x 20,9 x 17,5 in |
| Shipping Weight | 20,0 kg (44,1 lb) |

ORDERING INFORMATION

| Performance | | |
|------------------|--|----------------------|
| Model | Description | P/N |
| Contains | | |
| System | | |
| ALTEA-415 | | 10404850 |
| Replacement Part | s | |
| 15MI | Cone Transducer | 10214290 |
| F-AL415 | Filter | 30008821 |
| GM-15MI | Recone Kit | 20208270 |
| GM-M32 | Diaphragm | 20205055 |
| LAMP-F-21 | Lamp | 30000535 |
| M-32 | Compression Driver | 20208970 |
| Accessories | | |
| ANL-1 | Installation & Stacking Acc. | 10101010 |
| AX-112-5 | Installation & Stacking Acc. | 10102390 |
| FUN-AL715 | Transport Accessories | 10103781 |
| | | |
| TRD-6 | Installation & Stacking Acc. | 10104470 |
| | Installation & Stacking Acc. Installation & Stacking Acc. | 10104470 10104471 |

DIMENSIONS



