



## CPPS

Power Strip with up to 6 mains sockets. Equipped with powerCON® input receptacle and additional daisy chain powerCON® output receptacle.

### Features & Benefits

- Robust and safe plastic housing
- Reliable NEUTRIK® powerCON® recepticals
- High quality H07RN cable
- Daisy chaining
- Mounting option

### Article Variations

Article name	Details	Order code
CPPSF3-TT	3x Schuko with powerCON® TRUE1® TOP In and Out	1027441
CPPSF6-TT	6x Schuko with powerCON® TRUE1® TOP In and Out	1027442
CPPSE3-TT	3x Typ E with powerCON® TRUE1® TOP In and Out	1027596
CPPSE6-TT	6x Typ E with powerCON® TRUE1® TOP In and Out	1027597

## Technical Information

Product	
<b>Input device</b>	powerCON® TRUE1® TOP CPPSF3-TT
	powerCON® TRUE1® TOP CPPSF6-TT
	powerCON® TRUE1® TOP CPPSE3-TT
	powerCON® TRUE1® TOP CPPSE6-TT
<b>Output device</b>	3x Schuko with powerCON® TRUE1® TOP CPPSF3-TT
	6x Schuko with powerCON® TRUE1® TOP CPPSF6-TT
	3x Typ E with powerCON® TRUE1® TOP CPPSE3-TT
	6x Typ E with powerCON® TRUE1® TOP CPPSE6-TT
<b>Design</b>	Mobile / portable

Electrical	
<b>Contact resistance / protection class</b>	Protection class II
<b>Dielectric strength</b>	0,5 kV / mm
<b>Rated voltage</b>	250V AC
<b>Rated Current</b>	16A (USA: 20A)
<b>Number of electrical contacts</b>	2 + PE
<b>Phases</b>	single-phase

Mechanical	
<b>Dimensions</b>	272 x 60 x 46,6mm CPPSF[E]3-TT
	398 x 60 x 46,6mm CPPSF[E]6-TT
<b>Conductor cross section</b>	2,5mm <sup>2</sup>

Material	
<b>Housing</b>	PVC
<b>Color</b>	black

## Environmental

<b>Protection class</b>	IP20
<b>Temperature range</b>	-5 °C to +40 °C

## Mobile cable

<b>Weight</b>	0,42kg CPPSF[E]3-TT
	0,45kg CPPSF[E]6-TT