

| Product Type | RJ45 Adapter | |
|---------------|--------------|--|
| | | |
| Product Model | SE8FF-02-C6A | |
| | | |
| Customer Name | | |

| Manaufantanan | Prepared | Checked | Approved |
|---------------|----------|---------|----------|
| Manufacturer | | | |

| Queteman | Received | Checked | Confirmed |
|----------|----------|---------|-----------|
| Customer | | | |





| Product Type | RJ45 Adapter | |
|---------------|--------------|--|
| Product Model | SE8FF-02-C6A | |

Product Features

- > RJ45 feedthrough coupler for linking cables, CAT6a, PoE++
- Accommodates SE8MC-02-NEW
- Shorter length and more exquisite compact design
- > Complies with CAT6a according to TIA / EIA 568B and ISO / IEC 11801 standard
- > Very lightweight, fast and stable signal transmission





| Product Parameters | |
|--------------------|---------------|
| Item | Specification |
| Connection type | Adapter |

| Electrical Parameters | |
|--------------------------|---------------------------|
| Item | Specification |
| Contact resistance | < 10 mΩ |
| Rated current | 2 A |
| Rated voltage | 60 V |
| Insulation resistance | ≥ 0.5GΩ |
| Dielectric strength | 1 KV DC |
| Frequencyrange | 1~100 MHz |
| Transmission performance | CAT6a |
| Ethernet power supply | PoE++ accdg. IEEE 802.3bt |





| Mechanical Parameters | |
|-----------------------|----------------------|
| Item | Specification |
| Insertion force | ≤ 20 N |
| Service life | > 1000 mating cycles |
| Locking device | Latch lock |

| Material and Environmental Parameters | |
|---------------------------------------|---------------|
| Item | Specification |
| Contacts | Copper alloy |
| Insert | РВТ |
| Contact surface | Au |
| Panel | Zinc alloy |
| Temperature range | -30°C ~ +80°C |
| Protection degree | IP65 |

| Standards and Certifications | |
|------------------------------|------------------------|
| Standards | TIA/EIA 586B, IEC11801 |





Product Drawing 28.00±0.50 (55.15)G seetronic (45.95)PUSH (Φ) 6 9 33.10±0.50 (37.70) Adapter ннннннн CATE SE8FF-02-C6A (4 (seetronal) Unit: mm

sales@seetronic.com www.seetronic.com



Packaging Method

PE bag packing, 1 pc per bag

50 pcs per inner carton, 5 inner cartons per master carton (250 pcs per master carton)

Accessory No accessories Back fastener plate Screws Waterproof gasket

