



- 3-point Deco Truss
- perfect for shop fitting or decoration of clubs, bars, etc.
- with connection kit
- Diameter main tube: 18 mm
- Wall thickness main tube: 1 mm
- Outer distance main tube: 210 mm
- Diameter brace: 5 mm
- max. distributed line load: 100 kg
- Material: steel S235JR
- Colour: black
- Length: 25 cm (item no. 504299 Deco Truss 25 cm black)  
50 cm (item no. 485445 Deco Truss 50 cm black)  
75 cm (item no. 485447 Deco Truss 75 cm black)  
100 cm (item no. 485438 Deco Truss 100 cm black)  
150 cm (item no. 485440 Deco Truss 150 cm black)
- Weight: 1.1 kg (item no. 504299 Deco Truss 25 cm black)  
2.1 kg (item no. 485445 Deco Truss 50 cm black)  
2.5 kg (item no. 485447 Deco Truss 75 cm black)  
2.8 kg (item no. 485438 Deco Truss 100 cm black)  
4.5 kg (item no. 485440 Deco Truss 150 cm black)



- Deco Truss Base Plate (item no. 485562)
- Base plate for Stageworx Deco Truss system
- perfect for shop fitting or decoration of clubs, bars, etc.
- with connection kit
- Material: steel S235JR
- Colour: black
- Dimensions (W × H × D): 290 mm × 45 mm × 290 mm
- Weight: 2.5 kg



- 3-point Deco Truss
- 2-way corner 90° (item no. 485555 Deco Truss 2-Way 90° Corner)
- perfect for shop fitting or decoration of clubs, bars, etc.
- with connection kit
- Diameter main tube: 18 mm
- Wall thickness main tube: 1 mm
- Outer distance main tube: 210 mm
- Diameter brace: 5 mm
- max. distributed line load: 100 kg
- Material: steel S235JR
- Colour: black
- Dimensions (W × H × D): 354 mm × 354 mm × 183 mm
- Weight: 2.5 kg



- 3-point Deco Truss
- 3-way corner 90° (item no. 485560 Stageworx Deco Truss 3-Way 90° Corner)
- perfect for shop fitting or decoration of clubs, bars, etc.
- with connection kit
- Diameter main tube: 18 mm
- Wall thickness main tube: 1 mm
- Outer distance main tube: 210 mm
- Diameter brace: 5 mm
- max. distributed line load: 100 kg
- Material: steel S235JR
- Colour: black
- Dimensions (W × H × D): 350 mm × 315 mm × 350 mm
- Weight: 2.5 kg



- 3-point Deco Truss
- 3-way T-piece (item no. 485571 Stageworx Deco Truss T-Piece)
- perfect for shop fitting or decoration of clubs, bars, etc.
- with connection kit
- Diameter main tube: 18 mm
- Wall thickness main tube: 1 mm
- Outer distance main tube: 210 mm
- Diameter brace: 5 mm
- max. distributed line load: 100 kg
- Material: steel S235JR
- Colour: black
- Dimensions (W × H × D): 500 mm × 354 mm × 183 mm
- Weight: 2.5 kg

**Accessories**

- LBTA Deco Truss Adaptor Ø28 mm (item no. 366815)


**Load table**

Span	Uniformly distributed load
m	kg/m
1.5	15
3	8.8
4	4.6
5	2.7
6	1.6

The selfweight of the truss is considered in the load table.

**!** The truss must not be used for stage assembly or professional applications, because it has got no test certificate.



The truss system is used for stable mounting of spotlights for decoration purposes. Any other use or use under other operating conditions is considered to be improper and may result in personal injury or property damage. No liability will be assumed for damages resulting from improper use.

This product may be used only by persons with sufficient physical, sensorial, and intellectual abilities and having corresponding knowledge and experience. Other persons may use this device only if they are supervised or instructed by a person who is responsible for their safety.

Ensure that plastic bags, packaging, etc. are properly disposed of and are not in the reach of babies and young children. Choking hazard!

The mounting of the truss system may only be carried out by qualified and competent experts. Observe the locally applicable regulations. Depending on the site (club, exhibition booth), observe the valid mounting regulations applicable on the particular site. All constructional components must be subjected to a visual inspection before assembly begins.

When falling off an unsuitable climbing assistance, you could be injured or be caught by falling objects. Use a suitable working platform or a sturdy ladder for mounting the truss system or the spotlights. Place the working platform or the ladder on a flat and stable ground.



When the truss system is installed on soft or uneven ground, the truss system may tip over and cause injuries and property damage. Install the truss system only on even and solid surfaces and use only suitable securing material (for example steel ropes).

Use only suitable and sufficiently dimensioned mounting material and stands for the mounting.

Depending on the use, it may be necessary to install additional and independent securing systems using only sufficiently dimensioned mounting material.

In case of excessive or one-sided loading, the load carrying capacity of the truss system may be affected, causing injury and property damage. Never exceed the specified maximum load for the truss.



For the packaging, environmentally friendly materials have been chosen that can be supplied to normal recycling. Ensure that plastic bags, packaging, etc. are properly disposed of. Do not just dispose of these materials with your normal household waste, but make sure that they are collected for recycling. Please follow the notes and markings on the packaging.