


M25AS



GLOBAL TRUSS M25AS TRUSS SYSTEM

Global Truss stands for highest quality and reliability.

The M25AS decoration and exhibition truss varies from other three point system because of its screwing connection, its low weight and the shipping volume. The single pieces are fixed together with screwed cartridges.

The usage of the M25AS truss can be found in exhibitions, shops, events and fixed installations.


TECHNICAL DATA

Colour	Aluminum
Compability	Astralite
TÜV-Certificate	Yes
System	3-point
Dimensions	26,6 cm
Diameter main pipe	50,80 mm
Wall thickness main pipe	1,60 mm
Wall thickness Brace	1,60 mm
Diameter Brace	12,70 mm
Material	AlMgSi F31
Connectors	included



INCLUDING

3 X



LOAD TABLE

Span	Uniform distribution load	Deflection	Center point load	Deflection	point load in third-point	Deflection	point load in quarter-point	Deflection	point load in fifth-point	Deflection
m	kg / m	cm	kg	cm	kg	cm	kg	cm	kg	cm
4,00	85,7	0,8	170,3	0,6	127,5	0,8	85,7	0,7	71,4	0,8
5,00	54,0	1,2	133,6	1,0	101,0	1,2	67,3	1,2	56,1	1,2
6,00	36,7	1,8	109,1	1,4	81,6	1,8	54,0	1,7	45,9	1,8
7,00	25,5	2,4	90,8	2,0	68,3	2,4	45,9	2,3	37,7	2,4
8,00	19,4	3,1	77,5	2,6	58,1	3,2	38,8	3,0	31,6	3,2
9,00	14,3	4,0	66,3	3,3	49,0	4,1	32,6	3,8	27,5	4,0
10,00	11,2	4,9	57,1	4,2	42,8	5,0	28,6	4,7	23,5	5,0

The weight of the truss is considered in the load table.

Technical changes and errors are reserved

